

# Speakers



## Lay-In Speaker SP-628L

SP-628L 2-Way, Lay-in Ceiling Speaker Assembly

### Specifications

|                            |                                                       |
|----------------------------|-------------------------------------------------------|
| Frequency Range            | 120 Hz to 21 kHz, $\pm$ 6 dB                          |
| Power                      | 30 Watts Continuous                                   |
| Sensitivity                | 87 dB SPL (1W/1M)                                     |
| Impedance                  | 8 $\Omega$                                            |
| Nominal Coverage           | 90° x 90°                                             |
| LF Driver                  | 6.5" Cone Driver                                      |
| Magnet                     | 10 oz                                                 |
| HF Driver                  | High efficiency 1" domed tweeter                      |
| Enclosure Material         | Air Sealed Metal Backcan                              |
| Termination                | Screw terminals for secure speaker wire connection    |
| Mounting                   | Attached "T" Bar support                              |
| Dimensions (H x W x D)     | 12.25" x 23.75" x 6.25"<br>(13" with "T" Bar support) |
| Net Weight (ea)            | 8 lb                                                  |
| Shipping Weight (box of 4) | 39 lb                                                 |
| UL Requirement             | Meets UL 2043 criteria for plenum installation        |

### Features

- Complete speaker assembly (12" X 24")
- Perforated steel grill
- Heavy duty support for anti rattle or movement
- Attached adjoining T-bar
- Air Sealed Metal Back Can for an infinite baffle
- Screw terminal
- 3 pre-installed brackets for safety wire
- Completely painted, tile white
- No speaker assembly required
- Quick and efficient installation