

Speakers



Lay-In Speaker SP-628L

SP-628L 2-Way, Lay-in Ceiling Speaker Assembly

Specifications

Frequency Range	120 Hz to 21 kHz, \pm 6 dB
Power	30 Watts Continuous
Sensitivity	87 dB SPL (1W/1M)
Impedance	8 Ω
Nominal Coverage	90° x 90°
LF Driver	6.5" Cone Driver
Magnet	10 oz
HF Driver	High efficiency 1" domed tweeter
Enclosure Material	Air Sealed Metal Backcan
Termination	Spring terminals
Mounting	Attached "T" Bar support
Dimensions (H x W x D)	12.25" x 23.75" x 6.25" (13" with "T" Bar support)
Net Weight (ea)	8 lb
Shipping Weight (box of 4)	39 lb
UL Requirement	Meets UL 2043 criteria for plenum installation

Features

- Complete speaker assembly (12" X 24")
- Perforated steel grill
- Heavy duty support for anti rattle or movement
- Attached adjoining T-bar
- Air Sealed Metal Back Can for an infinite baffle
- Spring terminal for quick and secure speaker wire connection
- 3 pre-installed brackets for safety wire
- Completely painted, tile white
- No speaker assembly required
- Quick and efficient installation